

TOOLS & EQUIPMENT

QUICK - REFERENCE GUIDE

ITEM	DETAILS	PAGE
:	ECOVERY EQUIPMENT: CHARGING, RECOVERY, RECYCLING, MULTI-FUNCTION STATIONS CHARGING CYLINDERS ("DIAL - A - CHARGE" CYLINDERS) MANIFOLD TEST GAUGES, LINES, MANIFOLD SPARES SCALES, REFRIGERANT WEIGHING VACUUM PUMPS AND SPARES	391 393 - 395 392
	ON: ELECTRONIC LEAK DETECTORS	
	NT: REFRIGERANT ANALYSERS THERMOMETERS: POCKET, DIGITAL, THERMO-COUPLE, INFRA-RED	399 400
- - - - - - - - - -	S AND SERVICE ITEMS: ACCESS FITTINGS, COUPLERS, SPARES COMPRESSOR REPAIR CYLINDERS: REFRIGERANT, REFRIGERANT RECOVERY DYE: LEAK DETECTION FLUSHING & FLUSH RECOVERY EQUIPMENT, FLUSH SOLVENT GAUGES: MANIFOLD SETS GAUGES: VACUUM TESTING HOSE CRIMPING TOOLS INJECTORS, OIL INSPECTION TOOL, FIBRE OPTIC O-RINGS: ACCESS VALVES AND COUPLERS O-RINGS: MANIFOLD AND VALVE REPAIR ORIFICE REMOVAL, CORE REMOVAL TOOLS SEALANTS, SYSTEM SEALANT SPRINGLOCK REPAIR TOOLS UNIONS: CYLINDER, MANIFOLD, VACUUM PUMP WRENCHES: SERVICE VALVE	407 - 408 401 398 402 393 402 404 - 405 403 404 395 394 406 403

and Recovery Charging **Equipment**





TO-73210 AIR-CHIEF **DIGITAL CHARGING STATION**



REFCO HAND - CARRY DIGITAL CHARGING STATION



ROBINAIR DIGITAL CHARGING STATION 2-STAGE VACUUM PUMP

TO-73207: 28 lpm vacuum pump TO-73208: 94 lpm vacuum pump

Digital scales allow charging with specified amounts of refrigerant accurately.

RECOVERY STATIONS





TO-73270 - CR300E RECOVERY STATION **OIL-FILLED COMPRESSOR**



TO-73272 CR500E TO-73277 AR500E



RECOVERY ONLY RECOVERY / RECYCLE OIL-LESS COMPRESSOR


Robinair




ROBINAIR RECOVERY STATION (LIMITED STOCK)



ROBINAIR MINIMAX-E RECOVERY STATION TO-73250 RECOVERY ONLY





TO-73430 ROBINAIR RECYCLE UNIT CAN BE USED IN CONJUNCTION WITH MOST ROBINAIR RECOVERY STATIONS. (TO-73257 ILLUSTRATED)

NOTE: All current model Robinair Recovery Stations have oil-less compressors

Charging and Recovery Equipment

RECOVERY-RECYCLE-RECHARGE STATIONS



TO-73324
ROBINAIR AC350-2K
4 in 1 SEMI-AUTOMATIC
UNIT WITH BUILT IN
GAUGES

TO-73335 ROBINAIR 34701-2K


FULLY AUTOMATIC UNIT WITH INTERNAL SCALES AND TANK



Station Replacement Parts

PART No.	ITEM	TYPE / APPLICATION	STATION	OEM APPLICATION DETAILS
TO-18830	COMPRESSOR	RECLAIM, 1/3 hp	TO-73242	ROBINAIR No. RA17411
TO-28385 TO-28392 TO-28410 TO-28417	FILTER FILTER FILTER FILTER	RECYCLING RECYCLING RECYCLING RECYCLING	TO-73255 TO-73295 TO-73390 TO-73422	ROBINAIR No. 17130 ROBINAIR No. 17430 ROBINAIR No. 34430 ROBINAIR No. 17678
TO-31495	GASKET (set of 2)	LIQUID RECYCLING PUMP		ROBINAIR No. RA17068
TO-73650 TO-73680 TO-73720 TO-73750	SWITCH, POWER SWITCH, POWER SWITCH, PRESSURE SWITCH, VACUUM	RECLAIM UNIT RECLAIM UNIT RECLAIM UNIT RECLAIM UNIT		ROBINAIR No. RA17135 ROBINAIR No. RA17138 ROBINAIR No. RA17072 ROBINAIR No. RA18752
TO-81200	WHEEL	STATION	TO-73210	AIR-CHIEF

CHARGING CYLINDERS



TO-18350 ROBINAIR 34205A 2200 gram (5 lb) TO-18355 REFCO 4000 gram (10 lb)



Charging Cylinder Replacement Parts

PART No.	ITEM	TYPE / APPL	ICATION		OEM APPL	ICATION / DETAILS
TO-18328 TO-18334	CASING, CALIBRATED CASING, CALIBRATED	CHARGING CYLINDER CHARGING CYLINDER	REFCO ROBINAIR	4000 gram 4400 gram	REFCO ROBINAIR	SUITS TO-18355 113125
TO-31322 TO-31350 TO-31370	GASKET KIT GASKET KIT GASKET KIT	CHARGING CYLINDER CHARGING CYLINDER CHARGING CYLINDER	REFCO ROBINAIR ROBINAIR	4000 gram 2200 gram 4400 gram	REFCO ROBINAIR ROBINAIR	43699 10748RA
TO-31785	GAUGE, R12/R134a NOTE: TO-31785 REPLA	CHARGING CYLINDER CES ORIGINAL TO-31850	REFCO AND TO-	4400 gram 31854 R12 (CO AND ROBINAIR DOES R12 & R134
TO-70700	SIGHT GLASS	CHARGING CYLINDER	ROBINAIR	4400 gram	ROBINAIR	43291

Charging and Recovery Equipment

REFRIGERANT WEIGHING SCALES



remote read-out20 gram increments,

• 50 kg total capacity (including cylinder)

TO-69110 AIR - CHIEF ELECTRONIC WEIGHING SCALES



view of TO-69110 scale head showing transformer plug provision



TO-15184 9 volt battery for scale head



TO-61344 OPTIONAL POWER PACK (9-Volt) for TO-69110



TO-69302 ROBINAIR ELECTRONIC WEIGHING SCALES



TO-69306

ROBINAIR

PROGRAMMABLE

CHARGING / RECOVERY

METER

- 100 kg total capacity (including cylinder)
- remote read-out
- battery operated
- · 4 gram increments
- auto zero
- Charging and Recovery Capabilities
- 100 kg total capacity (including cylinder)
- remote read-out
- battery operated
- 4 gram increments Compact, completely portable
- Automatic Charging and Recovery Operations

VACUUM PUMPS



TO-62190 JAVAC MINIVAC - 2 VACUUM PUMP 2-STAGE



TO-62234
REFCO VACUUM PUMP
30 lpm 2-STAGE
(discontinued, replaced by
TO-62260)



TO-62260 REFCO VACUUM PUMP 35 lpm 2-STAGE



TO-62265 REFCO VACUUM PUMP 65 lpm 2-STAGE



TO-62297 REFCO VACUUM PUMP 150 lpm 2-STAGE



ROBINAIR 28 Ipm VACUUM PUMP TO-64028 28 Ipm, SINGLE STAGE TO-64128 28 Ipm, TWO STAGE



ROBINAIR 93 & 142 lpm VACUUM PUMPS TO-64194 93 lpm, TWO STAGE TO-64210 142 lpm, TWO STAGE

Charging Recovery **Equipment** and

VACUUM PUMPS ... cont'd

Vacuum Pump Selection Guide

PART No	o. BRAND	MODEL	MOTOR SIZE	CAPACITY (lpm)	VACUUM CAPABILITY	REFRIG. TYPE	OTHER INFORMATION
TO-6219		MINIVAC-2				R-12 / R-134a	ROTARY, TWO - STAGE
TO-6226		RL 2	1/5 H P	35	15 microns	R-12 / R-134a	ROTARY, TWO - STAGE
TO-6226	5 REFCO	RL 4	1/4 H P	65	15 microns	R-12 / R-134a	ROTARY, TWO - STAGE
TO-6229	7 REFCO	RL 8	1/2 H P	150	15 microns	R-12 / R-134a	ROTARY, TWO - STAGE
TO-6402	8 ROBINAIR	34117	1/8 HP	28	50 microns	R-12 / R-134a	DISCONTINUED
TO-6412	8 ROBINAIR	15296	1/8 HP	28	50 microns	R-12 / R-134a	ROTARY, TWO - STAGE
TO-6419	4 ROBINAIR	15444	1/3 H P	93	20 microns	R-12 / R-134a	ROTARY, TWO - STAGE
TO-6421	0 ROBINAIR	15605	1/3 H P	142	20 microns	R-12 / R-134a	ROTARY, TWO - STAGE

NOTE: FOR THE PURPOSE OF EVACUATION OF AN AIR CONDITIONING SYSTEM, A VACUUM PUMP MUST BE CAPABLE OF PULLING A VACUUM OF 200 MICRONS OR LESS TO VAPORIZE AND EXTRACT MOISTURE AT NORMAL TEMPERATURES.

Vacuum Pump Replacement Parts

ITEM	MAKE	MODEL	PART No.
BASE, BASE, HANDLE, HANDLE (INCLUDES SWITCH & CORD) HANDLE JOINT, RUBBER FLEXIBLE DRIVE SIGHT GLASS SIGHT GLASS SIGHT GLASS	ROBINAIR ROBINAIR REFCO ROBINAIR ROBINAIR JAVAC JAVAC REFCO ROBINAIR	15024, 15044, 15405, 15601, 15605 15113, 15117, 34117 ROY-2 15024, 15044, 15405, 15601, 15605 15296 DS40 DS40 ROY-2 15117 ROY-2	TO-15120 TO-15127 TO-33800 TO-33805 TO-33812 TO-37300 TO-70950 TO-70962 TO-70975 TO-79825
VENT `	ROBINAIR	63117	TO-80010



REFCO FRONT WHEEL, 2-WAY, MULTI-REFRIGERANT MANIFOLD. SUPPLIED COMPLETE WITH 1830mm LINES AND R134a COUPLERS.

MANIFOLD GAUGE SETS





REFCO FRONT WHEEL, 4-WAY, MULTI-REFRIGERANT MANIFOLD. SUPPLIED COMPLETE WITH 1830mm LINES AND R134a COUPLERS.

Manifold Selection Guide

PART No.	BRAND	COUPLERS.	MANIFOLD TYPE		GING LINES LENGTH		OTHER INFORMATION
TO-51080	REFCO	R134a, INCLUDED	FRONT WHEEL	YES	1830 mm		2-WAY MANIFOLD; BELLOWS GAUGES
TO-51085	REFCO	R134a, INCLUDED	FRONT WHEEL	YES	1830 mm	YES	4-WAY MANIFOLD; BELLOWS GAUGES
TO-51095	REFCO	R134a, INCLUDED	FRONT WHEEL	YES	1830 mm	YES	4-WAY WITH LIQUID FILLED GAUGES




Manifold Replacement Gauges



TYPICAL PRESSURE GAUGE

ITEM	TYPE	BRAND	DIAL AND CA	LIBRATION	GAUGE TYPE	PART No.
GAUGE, MANIFOLD	COMPOUND	ROBINAIR	R12 DIAL	Kpa / psi	BOURDON TYPE BOURDON TYPE BELLOWS TYPE BOURDON TYPE BOURDON TYPE BELLOWS TYPE	TO-31765
GAUGE, MANIFOLD	COMPOUND	REFCO	R134a DIAL	Kpa / psi		TO-31783
GAUGE, MANIFOLD	COMPOUND	REFCO	R134a DIAL	Kpa / psi		TO-31785
GAUGE, MANIFOLD	PRESSURE	ROBINAIR	R12 DIAL	Kpa / psi		TO-31820
GAUGE, MANIFOLD	PRESSURE	REFCO	R134a DIAL	Kpa / psi		TO-31833
GAUGE, MANIFOLD	PRESSURE	REFCO	R134a DIAL	Kpa / psi		TO-31835

Manifold - Test Gauge Sets and Spares



















Manifold Replacement Parts

ITEM	MODEL APPLICATION AND OTHER INFOR	RMATION	PART No.
HANDWHEEL HANDWHEEL HANDWHEEL	CPS - MOST MODELS REFCO - ALL MODELS ROBINAIR - MOST MODELS	1 ONLY (SET OF 4) (SET OF 2)	TO-34004 TO-34010 TO-34025
SEAL KIT, MANIFOLD SEAL KIT, MANIFOLD SEAL KIT, MANIFOLD AND LINES SIGHT GLASS STEM, MANIFOLD VALVE REPAIR STEM, MANIFOLD VALVE REPAIR	CPS - SUITS MOST CPS ROBINAIR - SUITS MOST ROBINAIR REFCO - SUITS MOST REFCO ROBINAIR - SUITS MOST ROBINAIR REFCO - SUITS MOST ROBINAIR REFCO - SUITS MOST REFCO	MANIFOLDS MANIFOLDS MANIFOLDS MANIFOLDS MANIFOLDS MANIFOLDS	TO-70468 TO-70480 TO-70500 TO-70940 TO-73500 TO-73501

MANIFOLD CHARGING LINES







NOTE: COUPLERS ARE NOT INCLUDED

PART No.	TYPE	COLOUR	LENGTH	FITTINGS I	MANUFACTURER
TO-40212 TO-40312 TO-42472 TO-42772 TO-42972 TO-43172 TO-43372 TO-47120 TO-48120 TO-49120 TO-49236Y TO-49372B TO-49372R	STANDARD STANDARD STANDARD STANDARD STANDARD QUICK-SEAL QUICK-SEAL STANDARD STANDARD STANDARD STANDARD STANDARD	BLUE RED BLUE RED YELLOW BLUE RED YELLOW BLUE RED YELLOW BLUE RED YELLOW YELLOW BLUE RED YELLOW	300 mm 300 mm 1830 mm 1830 mm 1830 mm 1830 mm 1830 mm 3050 mm 3050 mm 3050 mm 915 mm 1830 mm	1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/4" 1/4" - 1/2" ACME ACME - M14 ACME - M14	AIR-CHIEF AIR-CHIEF REFCO REFCO REFCO ROBINAIR ROBINAIR ROBINAIR REFCO REFCO REFCO REFCO REFCO REFCO REFCO REFCO
TO-49372Y TO-49420B TO-49420R TO-49420Y		YELLOW BLUE RED YELLOW	1830 mm 3050 mm 3050 mm 3050 mm	ACME - ACME ACME - M14 ACME - M14 ACME - ACME	REFCO REFCO REFCO REFCO

NOTES:

- 1. LENGTHS OF CHARGING LINES ARE NOMINAL AND MAY VARY SLIGHTLY.
- ALL REFCO AND ROBINAIR CHARGING LINES ARE WARRANTED FOR 12 MONTHS AGAINST FAULTY MANUFACTURE AND ARE DESIGNED FOR WORKING PRESSURES UP TO 3,500 kpa (500 psi), WITH A BURST PRESSURE OF 17,500 kpa (2,500 psi).
- $3. \ \ 1/4" \ LINES \ SUIT \ STANDARD \ 1/4" \ MF \ (7/16-20 \ UNF). \ ADAPTORS \ FOR \ 3/16" \ MF \ ACCESS \ VALVES \ ARE \ AVAILABLE.$
- 4. ACME LINES SUIT STANDARD 1/2" MALE ACME FITTINGS.

Manifold - Test Gauge Sets and Spares

R12 ACCESS ADAPTORS & COUPLERS




STANDARD STRAIGHT R-12 **ACCESS COUPLERS**

TO-12010 R-12 3/16"FF - 1/4" MF TO-12500 R-12 1/4" FF - 1/4" MF



STANDARD 90 deg. R-12 **ACCESS COUPLERS**

TO-12090 R-12 3/16"FF - 1/4" MF TO-12590 R-12 1/4" FF - 1/4" MF





ROBINAIR R-12 ANTI-BLOWBACK **ACCESS COUPLERS**

TO-13185 R-12 3/16"FF - 1/4" MF TO-13200 R-12 1/4" FF - 1/4" MF

TO-13250 R-12 1/4" FF - 1/4" MF LOW SIDE (BLUE HOSE) TO-13255 R-12 1/4" FF - 1/4" MF HIGH SIDE (RED HOSE)

R134a ACCESS ADAPTORS & COUPLERS



R134a ACCESS COUPLER COMPACT TYPE. HANDWHEEL OPERATION.

TO-14128 - DISCHARGE TO-14138 - SUCTION (Air - Chief)



R134a ACCESS COUPLER COMPACT TYPE. HANDWHEEL OPERATION.

TO-14130 - DISCHARGE TO-14140 - SUCTION



R134a 90 deg. ACCESS COUPLER COMPACT TYPE HANDWHEEL OPERATION

TO-14134 - DISCHARGE TO-14236 - SUCTION



TO-13284 R134a IN-LINE BALL VALVE 1/2" MALE ACME - 1/2" FEM. ACME

ACCESS ADAPTOR DEPRESSORS



R-12 ACCESS FITTING **DEPRESSORS**

TO-25050 - 3/16" (PACK OF 6) **TO-25051** - 3/16" (PACK OF 10)

TO-25150 - 1/4" (PACK OF 6)

ACCESS ADAPTOR GASKETS & O-RINGS



TO-31050 EARLY ANTI-BLOWBACK SEAL-FLAT SECTION (DISCONTINUED)



R-12 ACCESS FITTING GASKETS

TO-31070 - 3/16" ROBINAIR (PACK OF 6) TO-31100 - 1/4" ROBINAIR (PACK OF 6) TO-31120 - 1/4" REFCO



TO-55900 REPLACEMENT O-RING FOR LATE TYPE TO-13185 (PACK OF 6)



TO-55934 O-RING KIT FOR COUPLERS TO-14128, TO-14130, TO-14134 TO-14138, TO-14140, TO-14136

NOTE: TO ASSIST IDENTIFICATION, THE O-RINGS ILLUSTRATED ABOVE ARE SHOWN ACTUAL SIZE.

Detection <u>Equipment</u> Leak

ELECTRONIC LEAK DETECTORS



TO-25265 CPS - L780B Leak - Seeker

SUITABLE FOR R134a, R-12, MOST CFC'S & HCFC'S

SENSITIVITY: 7 grams (1/4 oz) PER YEAR

FEATURES:

- INSTANT RESPONSE
- · AUDIBLE ALARM PLUS VISUAL RED INDICATOR
- . BUILT IN SUCTION PUMP
- VISUAL INDICATOR SHOWS REFRIGERANT CONCENTRATION
- · LOW BATTERY INDICATOR
- · AMBIENT CONDITION BALANCE ADJUSTMENT
- · ADJUSTABLE SENSITIVITY
- FLEXIBLE PROBE
- DESIGNED TO SAE J1627 SPECIFICATIONS

REPLACEMENT PARTS

SENSING ELEMENT - TO-28180 SENSING ELEMENT COVER - TO-75350

TO-25270 CPS - L790B Leak - Seeker

SUITABLE FOR R134a, R-12, MOST CFC'S AND HCFC'S

SENSITIVITY: 3 grams (1/10 oz) PER YEAR

FEATURES:

- INSTANT RESPONSE
- AUDIBLE ALARM, VISUAL RED INDICATOR (EITHER OR BOTH CAN BE SELECTED)
- VISUAL INDICATOR SHOWS REFRIGERANT CONCENTRATION
- **BUILT IN SUCTION PUMP**
- LOW BATTERY INDICATOR
- ADJUSTABLE SENSITIVITY
- AMBIENT CONDITION BALANCE ADJUSTMENT
- FLEXIBLE PROBE
- AUTOMATICALLY SWITCHES OFF WHEN NOT IN USE
- EARPHONE INCLUDED
- DESIGNED TO SAE J1627 SPECIFICATIONS

REPLACEMENT PARTS;

SENSING ELEMENT - TO-28180 SENSING ELEMENT COVER - TO-75350





TO-25285 **CPS-LS3000**

SUITABLE FOR R134a, R-12, MOST CFC'S AND HCFC'S

SENSITIVITY: 3 grams (1/10 oz) PER YEAR

FEATURES:

- INSTANT RESPONSE
- AUDIBLE HIGH OUTPUT ALARM WITH TONE CHANGE FUNCTION
- UNIQUE SELECTIVE FILTER DESIGN GIVES EXCELLENT RESISTANCE TO BACKGROUND CONTAMINANTS LIKE OIL AND COOLANT.
- VISUAL INDICATOR SHOWS REFRIGERANT CONCENTRATION IN "TACHOMETER" STYLE DISPLAY

 • LONG BATTERY LIFE ON STANDARD 'C' SIZE BATTERIES
- FULLY AUTOMATIC GAIN SELECTION
- RESET FUNCTION
- UNIQUE "GEAR SHIFT" STYLE LEAK SIZE INDICATOR FLEXIBLE PROBE
- DESIGNED TO SAE J1627 SPECIFICATIONS

REPLACEMENT PARTS;

SENSING ELEMENT - TO-75353

IMPORTANT NOTE:

ELECTRONIC DETECTORS MUST NOT BE USED WITH FLAMMABLE SUBSTANCES MOST ELECTRONIC LEAK DETECTORS DESIGNED FOR CFC'S AND R134a USE A HIGH TENSION SPARK IN THE SENSING TIP AND MUST NEVER BE USED TO DETECT FLAMMABLE SUBSTANCES SUCH AS LPG.

Detection Leak Equipment

ELECTRONIC LEAK DETECTORS



TO-25374 Model 5650A

SUITABLE FOR R134a, R-12, MOST CFC'S & HCFC'S

SENSITIVITY: 7 grams (1/4 oz) PER YEAR **FEATURES**:

- INSTANT RESPONSE

- INSTANT RESPONSE
 AUDIBLE ALARM PLUS VISUAL RED INDICATOR
 BUILT IN SUCTION PUMP
 VISUAL INDICATOR SHOWS REFRIGERANT CONCENTRATION
 LOW BATTERY INDICATOR
- AMBIENT CONDITION BALANCE ADJUSTMENT
- ADJUSTABLE SENSITIVITY
- FLEXIBLE PROBE
- DESIGNED TO SAE J1627 SPECIFICATIONS

REPLACEMENT PARTS: SENSING ELEMENT - TO-75364



TO-25382 **RX-1A High Tech**

SUITABLE FOR R134a, R-12, MOST CFC'S & HCFC'S

SENSITIVITY: 7 grams (1/4 oz) PER YEAR

FEATURES:

- ADVANCED DIGITAL SIGNAL PROCESSOR 2 SENSITIVITY LEVELS
- INSTANT RESPONSE
- VERY STABLE AND RELIABE
- AUDIBLE ALARM PLUS VISUAL RED BAR-GRAPH INDICATOR BUILT IN SUCTION PUMP
- VISUAL INDICATOR SHOWS REFRIGERANT CONCENTRATION
- LOW BATTERY INDICATOR ADJUSTABLE SENSITIVITY
- ONE TOUCH RESET AND KEYPAD CONTROLS
- FLEXIBLE STAINLESS STEEL PROBE
 DESIGNED TO SAE J1627 SPECIFICATIONS
- INCLUDES HEAVY DUTY CARRY CASE

REPLACEMENT PARTS: SENSING ELEMENT - TO-75364



TO-25388 XP-1A High Performance

SUITABLE FOR R134a, R-12, MOST CFC'S & HCFC'S

SENSITIVITY: 3 grams (0.1 oz) PER YEAR

FEATURES:

- ADVANCED DIGITAL SIGNAL PROCESSOR
- INSTANT RESPONSE
- 7 SENSITIVITY LEVELS AUDIBLE ALARM PLUS VISUAL TRI-COLOUR INDICATOR WITH 18 LEVELS FOR CLEAR INDICATION OF LEAK SIZE
- BUILT IN SUCTION PUMP BATTERY VOLTAGE TEST/INDICATOR 7 LEVELS OF SENSITIVITY
- I TOUCH RESET AND KEYPAD CONTROLS FLEXIBLE STAINLESS STEEL PROBE DESIGNED TO SAE J1627 SPECIFICATIONS

- HEAVY DUTY CARRY CASE INCLUDED

REPLACEMENT PARTS: SENSING ELEMENT - TO-75364



TO-25442 **ZX-1A** Heated Pentode

SUITABLE FOR R134a, R-12, MOST CFC'S & HCFC'S

SENSITIVITY: 3 grams (0.1 oz) PER YEAR

FEATURES:

- HEATED PENTODE OPERATION:
 REFRIGERANT SPECIFIC DETECTION

 - ELIMINATION OF FALSE ALARMS UNAFFECTED BY RAPID TEMPERATURE CHANGE
- INSTANT RESPONSE
- AUDIBLE ALARM PLUS VISUAL TRI-COLOUR INDICATOR BUILT IN SUCTION PUMP

- BOILT IN SUCTION POMP
 BATTERY VOLTAGE TEST / INDICATOR
 AMBIENT CONDITION BALANCE ADJUSTMENT
 2 LEVELS OF SENSITIVITY
 1 TOUCH RESET AND KEYPAD CONTROLS
 FLEXIBLE STAINLESS STEEL PROBE
 DESIGNED TO SAE J1627 SPECIFICATIONS

- HEAVY DUTY CARRY CASE INCLUDED

REPLACEMENT PARTS: SENSING ELEMENT - TO-75387

IMPORTANT NOTE:

ELECTRONIC DETECTORS MUST NOT BE USED WITH FLAMMABLE SUBSTANCES MOST ELECTRONIC LEAK DETECTORS DESIGNED FOR CFC'S AND R134a USE A HIGH TENSION SPARK IN THE SENSING TIP AND MUST NEVER BE USED TO DETECT FLAMMABLE SUBSTANCES SUCH AS LPG.

Leak Detection Equipment



Glo-Leak Ultra Violet Leak Detection System

5-diode, white head (optional extra)
5-diode UVA head (included)

MagniFocus 4

(optional extra)

TO-25658

MODULAR POCKET LAMP
WITH FLEXIBLE EXTENSION
(includes one 5 UVA diode head, order
5-diode white or MagniFocus4 heads

separately if required)

GLO-LEAK

TO-32100

THE VERSATILE LEAK DETECTION SYSTEM.

For use with most fluid leaks, including Air Conditioning, Refrigeration, Hydraulics, Cooling Systems and Fuel Systems.

TO-25658 GLO-LEAK POCKET ULTRA-VIOLET LAMP KIT IN MOULDED CARRY CASE TO-25665 GLO-LEAK 12 volt ULTRA-VIOLET LAMP KIT IN MOULDED CARRY CASE TO-25675 GLO-LEAK 240 volt ULTRA-VIOLET LAMP KIT IN METAL CARRY CASE

POCKET TYPE WITH FLEXIBLE PROBE 12v ONLY

TO-25665

12 volt

HIGH PERFORMANCE

U-V LAMP

240v ONLY

LAMP KITS INCLUDE SAFETY GLASSES (TO-32100)

Ultra-Violet Lamp Replacement Parts

PART No.	ITEM	TYPE	LAMP	APPLICATION / DETAILS
TO-28460	FILTER LENS	U - V (BLACK)	TO-25675	240 VOLT LAMP
TO-28485	FILTER LENS	U - V (BLACK)	TO-25665	12 VOLT LAMP
TO-28500	FILTER LENS	U - V (BLUE)	TO-25665	12 VOLT LAMP
TO-31940	GLOBE	U - V 100 WATT	TO-25665	12 VOLT LAMP
TO-31960	GLOBE	U - V 100 WATT	TO-25675	240 VOLT LAMP
TO-32100	GOGGLES	SAFETY, U - V	N - A	USE TO ENHANCE FLUORESCENCE
TO-33774	HANDLE	U - V LAMP	TO-25675	SUITS LATE TYPE LAMP
TO-34061	HEAD, 5 - DIODE UVA	U - V LAMP	TO-25658	SUITS MODULAR POCKET LAMP
TO-34063	HEAD, 5 - DIODE WHITE	U - V LAMP	TO-25658	SUITS MODULAR POCKET LAMP
TO-34065	HEAD, MAGNI FOCUS 4	U - V LAMP	TO-25658	SUITS MODULAR POCKET LAMP

Glo-Leak U-V Dye Selection Guide

TO-27412 Sachet - 12-shot pack (pack of 12 7.5ml sachets)



TO-27441 Cartridge, for use with TO-36115 injector



TO-27455 100 ml bottle, for use with TO-36100 injector



TO-27583, TO-27600, TO-27650, TO-27700, TO-27760 250 ml Bottle

1. Air Conditioning and Refrigeration Dye.

PART No.	FORMULA	PACK / CONTAINER TYPE	No. OF INJECTIONS	APPLICATION REFRIGERANT	/ COMPATABILITY LUBRICANT
TO-27412 TO-27441 TO-27444 TO-27452 TO-27455 TO-27583 TO-27600	CONCENTRATE STANDARD STANDARD CONCENTRATE CONCENTRATE STANDARD CONCENTRATE	CARTRIDGE CARTRIDGE (4-PACK) 50 ml BOTTLE (PACK of 2)	12 - SHOT 12 / 24 - SHOT ** 4 x 12 / 24 - SHOT ** 25 - SHOT 80 - SHOT	R12, R134a R12, R134a R12, R134a R12, R134a R12, R134a R12, R134a R12, R134a	MINERAL / ESTER / PAG MINERAL / ESTER / PAG
		** INJECTION AMOUNT CAN I	BE VARIED ON TO-3611	15 INJECTION (GUN

2. Automotive / Industrial Dye.

TO-27650	DYE,	AUTOMOTIVE	TRANSMISSION	250 ml
TO-27700	DYE,	AUTOMOTIVE, INDUSTRIAL	ENGINE (RADIATOR) COOLANT	250 ml
TO-27760	DYE,	AUTOMOTIVE, INDUSTRIAL	ENGINE OIL, HYDRAULIC OIL AND FUEL SYSTEMS.	250 ml

Leak Detection **Equipment**

ULTRA - VIOLET LEAK DETECTORS



TO-36100 **INJECTOR GUN**

REPLACEMENT PARTS:

TO-19850 TO-22100 FEMALE COUPLER CALIBRATED CYLINDER

TO-38745 OVERHAUL KIT (INCLUDES CYLINDER)




TO-36115 INJECTOR GUN

FOR USE WITH TO-27441 CARTRIDGE.

- HOSE (TO-34095) IS INCLUDED.
- COUPLER IS NOT INCLUDED order TO-14236 if required

Test Equipment

REFRIGERANT ANALYSERS



TO-26462

REFRIGERANT DETECTOR.

THIS UNIT DETECTS AND IDENTIFIES: CFC's, HFC's, HCFC's, FLAMMABLES, AND NON-CONDENSABLES.

THE CONTENTS OF THE SYSTEM OR CONTAINER ARE VISIBLE ON A DIGITAL READ-OUT, AND THE INFORMATION CAN BE PRINTED OUT ON MOST COMPUTER PRINTERS.

ONLY A SMALL AMOUNT OF REFRIGERANT IS REQUIRED AND IDENTIFICATION TAKES A FEW SECONDS.

ACCESSORIES INCLUDED:

R12 and R134a CONNECTION BATTERY CLAMP ADAPTOR 12V CIGARETTE LIGHTER CORD IN-LINE FILTER OPERATOR'S MANUAL

REPLACEMENT FILTER: TO-28439



FEATURES:

- MICRO INFRARED SPECTROMETER DETECTION SYSTEM
- ONE BUTTON TESTING WITH TEST RESULTS IN 3-5 SECONDS IDENTIFIES AND MEASURES THE PERCENTAGE (PURITY) OF THE REFRIGERANT, INCLUDING R134a, R12, R22, AND HYDROCARBONS.
- AUDIBLE AND VISUAL ALARMS WHERE FLAMMABLE HYDROCARBONS ARE PRESENT.
- INDICATES PRESENCE OF BLENDS AND CONTAMINATED REFRIGERANTS. INDICATES PRESENCE AND PERCENTAGE OF AIR IN THE SYSTEM.
- PRINTER PORT FOR RETENTION OF RECORDS SUITS MOST PC PRINTERS. ALTITUDE COMPENSATION FEATURE ENSURES ACCURATE AIR MEASUREMENT.
- OPERATES ON 12 VOLT OPTIONAL 240 VOLT ADAPTORS AVAILABLE.
- UL LISTED TO SAE J1771

Test Equipment

DIAL and DIGITAL THERMOMETERS



TO-75090 DIAL TYPE THERMOMETER

FLEXIBLE PROBE, 100 mm DIAL TEMPERATURE RANGE: -40 °C. to 40 °C.

TO-75125

PROFESSIONAL DIGITAL THERMOMETER -40 °C. to 50 °C. (-40 °F. to 122 °F.)

- · COMPACT, STEEL PROBE ON FLEXIBLE WIRE LEAD
- FOUR DIGIT DISPLAY ON DIGITAL READ-OUT
- DISPLAYS °C. OR °F
- FAST OR SLOW TEMPERATURE SENSING SPEED (1 OR 15 SECOND SAMPLING CYCLE)
- HIGH & LOW LIMIT TEMPERATURE SETTING FUNCTION





TO-75100

DIAL TYPE POCKET THERMOMETER METAL PROBE

TEMP. RANGE: -40 °C. to 70 °C.



THERMO-COUPLE **THERMOMETER**

TO-75158

THERMO-COUPLE THERMOMETER SUPPLIED COMPLETE WITH ONE THERMO-COUPLE PROBE, QUICK AND EASY TO USE-IDEAL FOR CHECKING SUPERHEAT AND SUB-COOLING.

AN ESSENTIAL TOOL FOR THE MODERN AIR CONDITIONING TECHNICIAN.





REPLACEMENT PROBE: TO-61520

INFRA-RED THERMOMETERS



TO-75164

DELUXE INFRA-RED THERMOMETER FEATURES:

- LASER INDICATOR ENSURES TARGET ACCURACY
- PISTOL GRIP, EASY TO POINT
- INSTANT TEMPERATURE DISPLAY
- EASY TO READ BACK-LIT DIGITAL **DISPLAY**
- DISPLAYS °C. OR °F.
- LOW BATTERY INDICATOR
- TEMP. RANGE: -20 °C. to 500 °C.
- VIEW FIELD RATIO: 8:1

TO-75175

INFRA-RED THERMOMETER

FEATURES:

- LASER 8-POINT CIRCULAR INDICATOR **ENSURES TARGET ACCURACY**
- PISTOL GRIP, EASY TO POINT
- INSTANT TEMPERATURE DISPLAY
- EASY TO READ DIGITAL DISPLAY
- DISPLAYS °C. OR °F.
 CLEAR, BACK-LIT DIGITAL DISPLAY
- LOW BATTERY INDICATOR
- TEMP. RANGE: -32 °C. to 600 °C.
- HIGH LOW ALARM
- VIEW FIELD RATIO: 30:1
- CARRY CASE INCLUDED

Tools and Service General Items

BEAKER: OIL DRAIN



TO-15300 100 ml GRADUATED BEAKER IDEAL FOR OIL MEASUREMENT ETC.

CLEANER



TO-18375 500 ml ATOMISER

GLO-KLENS BIODEGRADABLE CLEANER AND DEGREASER. A SAFE AND VERSATILE CLEANER, THIS PRODUCT IS NON-TOXIC TO HUMANS AND ANIMALS AND HELPS TO REMOVE TAR, WAXES, ADHESIVES, FRESH PAINT AND MANY OTHER

IDEAL FOR CLEANING OFF GLO-LEAK TRACER DYES.

COMB: FIN REPAIR



TO-18740 FIN COMB MULTI-HEADED COMB SUITABLE FOR MOST CONDENSER AND EVAPORATOR FINS.

CUTTER: HOSE



TO-21500

ATCO KWIK-CUT HOSE CUTTER CUTS ALL R-12 AND R134a REFRIGERANT HOSE QUICKLY AND EASILY.

REPLACEMENT BLADE - TO-15500

CYLINDERS



PART No. CAPACITY VALVE ARRANGEMENT

10 kg SINGLE VALVE TO-22011

LIQUID PICK-UP TUBE TO-22025 22 kg SINGLE VALVE, 22 kg DUAL TO-22027

VALVES, SINGLE OUTLET VALVES, DUAL OUTLET TO-22044 25 kg DUAL

DEODORANT

CONCENTRATE IN 4" CAN MAKES IT PERFECT FOR THE GLOVE BOX



REDUCES AIR-BORNE **BACTFRIA**

TO-24900

HANDY SPRAY CAN (35 ml) THIS PRODUCT IS BIODEGRADABLE, AND HELPS TO PREVENT ODOURS AND MOULD IN THE EVAPORATOR COIL.

GIVE THE CUSTOMER A CAN TO PREVENT ANY FURTHER PROBLEMS.

Tools and Service Items General



FLUSHING EQUIPMENT

Flush Kit

TO-28760

AIR-CHIEF FLUSHING KIT INCLUDES CYLINDER, FLUSH GUN AND LINE FOR USE WITH TO-28724 FLUSHING SOLVENT. (FLUSHING SOLVENT IS NOT INCLUDED IN KIT)



ACCESSORIES and PARTS

ACCESS UNION FOR R134a TO-14450 REPLACEMENT FLUSH GUN: TO-32550 REPLACEMENT RUBBER TIP: TO-75230 SPARE CAN FOR FLUSH: TO-18160



TO-28724

FLUSHING SOLVENT - 5 kg CAN APPROVED FOR USE WITH R-12 AND R134a SYSTEMS.

WE DO NOT RECOMMEND ANY OTHER SOLVENT. MUST NOT BE USED WITH COMPRESSED AIR.

RECOMMENDED PROPELLANT IS NITROGEN.



NITROGEN REGULATOR (suits type 50 cylinders)



CONVERTER (converts old type regulators to suit type 50 cylinders)


TO-66344 NITROGEN REGULATOR

AN ECONOMICAL NITROGEN REGULATOR, IDEAL FOR USE WITH FLUSHING KITS WHEN USING NITROGEN AS A PROPELLANT.

SCREW THE FLUSH KIT HOSE DIRECTLY ONTO THE REGULATOR.

AN APPROVED REGULATOR MUST BE USED WITH COMPRESSED NITROGEN AT ALL TIMES.

Flush Recovery Unit



TO-28766 AIR-CHIEF FLUSH RECOVERY UNIT

CATCH AND REUSE SOLVENT!

THIS SIMPLE. EFFECTIVE DEVICE ATTACHES TO FITTINGS WITHOUT TOOLS, USING A RUBBER MEMBRANE INFLATED BY A FINGER-SIZE PUMP.

GAUGES, VACUUM TESTING

THE VACUUM GAUGE IS AN ESSENTIAL TOOL FOR ACCURATE MEASUREMENT AND TESTING OF THE LEVEL OF VACUUM IN A SYSTEM, AND FOR CHECKING VACUUM PUMPS.

TO-31890 **REFCO**

DIGITAL VACUUM GAUGE

- reads in seven units: microns, PSI, in/Hg, mbar, Pascals, Torr or mTorr
- hook for easy positioning
- low numeric resolution
- accurate reading

EIII VA

TO-31895 **ROBINAIR**


DIGITAL VACUUM GAUGE

- · reads down to 10 microns
- · long lead and magnetic strip for convenient positioning
- low numeric resolution
- · accurate reading



General Tools and Service Items

INJECTORS



TO-36234 OIL INJECTOR R134a - ACME




GREASE, DEEP VACUUM



TO-32250
A SPECIAL LOW VAPOUR PRESSURE GREASE FOR USE IN VACUUM VALVES, CHARGING MANIFOLDS, ETC.

MANUAL, SERVICE



TO-52642
AIR-CHIEF BASIC SERVICE AND TRAINING MANUAL

MIRROR, INSPECTION



TO-54012

TELESCOPIC POCKET INSPECTION MIRROR EXTENDS TO 200mm.

SEALANT, LEAK-LOCK



TO-70645

LEAK-LOCK HOSE FITTING SEALANT.

IF USED SPARINGLY, THIS SEALANT IS SAFE FOR USE ON HOSE FITTINGS IN R-12 SYSTEMS. IT IS **NOT** DESIGNED FOR USE WITH SOME LUBRICANTS SUCH AS PAG

SEALANT, O-RING



TO-70647

HOSE FITTING AND O-RING SEALANT.

A SAFE SEALANT FOR USE ON O-RINGS AND HOSE FITTINGS IN R134a SYSTEMS.

SEALANT, SYSTEM



AIRCO-SEAL PRO KIT A SAFE SEALANT FOR USE IN R134a SYSTEMS. KIT INCLUDES CAN OF SEALANT, TAP AND HOSE

Tools and General Service Items

SYRINGES



TO-73950 TO-73954 UNIVERSAL 10 ml UNIVERSAL 60 ml

THESE SYRINGES ARE USEFUL FOR INJECTING SMALL OR MEASURED AMOUNTS OF SUCH THINGS AS DYE OR LUBRICANT.

VALVE - QUICK COUPLER



TO-79650

QUICK COUPLER HAND VALVE 1/4" MALE FLARE - 1/4" FEM. FLARE

TOOL, INSPECTION (FIBRE OPTIC)



TO-50861 CLIP-ON MAGNET (for 5.8mm probe)

TO-54124 **CLIP-ON MIRROR** (for 5.8mm probe)

TOOL

TO-31924 HALOGEN GLOBE TO-75644 450mm x 5.8mm dia. probe TO-75647 450mm x 10.6mm dia. probe

ILLUMINATED FIBRE OPTIC TYPE INSPECTION TOOL

AN INVALUABLE, VERSATILE INSPECTION TOOL FOR AIR CONDITIONING TECHNICIANS, MECHANICS, AND MANY OTHER USES.

FEATURES:

- LAMP BUILT INTO THE TIP ILLUMINATES DARK AREAS AT THE TOUCH OF A BUTTON.
- 450mm FLEXIBLE FIBRE OPTIC PROBE (900mm probe model also available)
- INTEGRATED FOCUS ADJUSTMENT
- SEALED LENS AND CABLE ARE SUBMERSIBLE
- SUPPLIED WITH A STURDY, HARD PLASTIC CASE

©

OPTIONAL ACCESSORIES FOR 5.8mm PROBE:

- MAGNET ATTACHMENT (clip-on) TO-50861
 MIRROR ATTACHMENT (clip-on) TO-54124


SPARE PARTS:

REPLACEMENT HALOGEN GLOBE: TO-31924 (suits 5.8mm and 10.6mm probes)



BENCH STAND KIT (INCLUDED)

General Tools and Service Items



TOOLS, CRIMPING, BEADLOCK

Standard Beadlock Crimper

TO-75602

ATCO BEADLOCK CRIMPING TOOL FOR USE WITH BEADLOCK TYPE HOSE FITTINGS.

INCLUDES A COMPLETE SET OF DIES FOR STANDARD DIAMETER HOSE.

Beadlock Crimper Replacement Parts

CARRIER, CARRIER, CARRIER, DIE, DIE, DIE, DIE, DIE, DIE, DIE, DIE	SUIT # 6 SUIT # 8 SUIT #10 SUIT #12 STANDARD STANDARD STANDARD REDUCED REDUCED REDUCED REDUCED REDUCED TEFLON LATCH	DIE (set of 2 pcs) DIAMETER HOSE	BLACK BLUE GREEN YELLOW No. 6 No. 8 No. 10 No. 12 No. 6 No. 8 No. 10 No. 12	TO-18306 TO-18308 TO-18310 TO-18312 TO-27326 TO-27328 TO-27330 TO-27332 TO-27346 TO-27348 TO-27350 TO-27352 TO-32276 TO-60560



DIE CARRIER

Manual / Hydraulic Beadlock Crimpers



TO-75606

HYDRAULIC BEADLOCK CRIMPING TOOL FOR USE WITH BEADLOCK TYPE HOSE FITTINGS.

INCLUDES A COMPLETE SET OF DIES FOR BOTH STANDARD AND REDUCED DIAMETER BARRIER HOSE.

Replacement Parts

DIE SET, DIE SET, DIE SET, DIE SET, DIE SET, DIE SET,	Black Purple Red Orange Yellow Blue	# 6 # 8 # 10 # 10 # 12	reduced hose std. & # 8 reduced hose standard hose reduced hose standard hose reduced hose	TO-27115 TO-27116 TO-27118 TO-27119 TO-27120 TO-27121
DIE SET,	Green	# 12	standard hose	TO-27122
HEAD, PIN, RAM,	Crimper Yoke pin Hydraulid		Chain assembly	TO-34047 TO-60425 TO-66185



TO-75609

MANUAL/HYDRAULIC BEADLOCK CRIMPING TOOL FOR USE WITH BEADLOCK TYPE HOSE FITTINGS.

INCLUDES A COMPLETE SET OF DIES TO SUIT BOTH STANDARD AND REDUCED DIAMETER BARRIER HOSE.

FEATURES INCLUDE:

- COMPACT, MODULAR TOOL
- · LIGHTWEIGHT ALLOY BODY
- · CAN BE HAND-HELD OR BENCH MOUNTED
- · CONVERTS TO HYDRAULIC OPERATION EASILY
- REPLACEMENT OF DIES IS QUICK AND SIMPLE
 NO SPECIAL TOOLS REQUIRED

Replacement Parts


CARRIER, White	#	6	reduced hose	TO-18265
CARRIER, Yellow	#	6	std. & # 8 reduced hose	TO-18266
CARRIER, Red	#	8	standard hose.	TO-18268
CARRIER, Black	# 1	10	reduced hose.	TO-18269
CARRIER, Green	# 1	10	std. & #12 reduced hose	TO-18270
CARRIER, Blue	# 1	12	standard hose.	TO-18272

• • NOTE: carriers are supplied as a set (2 pcs)

DIE SET, DIE SET, DIE SET, DIE SET, DIE SET, DIE SET,	Yellow # Red # Black # 1 Green # 1	6 8 0 0	reduced hose std. & # 8 reduced hose standard hose. reduced hose. std. & #12 reduced hose standard hose.	TO-27225 TO-27226 TO-27228 TO-27229 TO-27230 TO-27232
- ,	Hydraulic ar			TO-66197

General Tools and Service Items





TO-75625

SPRINGLOCK HOSE FITTING REPAIR TOOL. KIT COMPRISES SET OF No.6, 8, 10, AND 12

TOOL, ORIFICE REMOVER



TO-75672

ORIFICE TUBE REMOVER.
COMBINATION TOOL, SUITS FORD AND GM ORIFICE TUBES

TOOL, TUBE BENDER



FOR USE WITH COPPER AND ALLOY TUBING SUITS: 3/16", 1/4", 5/16" AND 3/8" TUBING

TOOL, VALVE CORE

TO-75875

CORE REMOVER FOR STANDARD AIR CONDITIONING ACCESS VALVE CORES.



TO-75881

CORE REMOVING TOOL FOR HIGH-FLOW AIR CONDITIONING ACCESS VALVE CORES. SUITS MOST STANDARD AND HIGH-FLOW CORES

WRENCHES



TO-81360

4-WAY RATCHET WRENCH 3/16" - 1/4" AND 5/16" - 3/8"




Unions

CYLINDER, MANIFOLD & VACUUM PUMP




REFRIGERANT CYLINDER UNION

3/4" FEM. GAS- 1/4" MF TO-77300 3/4" FEM. GAS- 1/2" ACME TO-77334




TO-77400

CHARGING LINE UNION 1/4"MF - 1/4"MF




TO-77432

MANIFOLD UNION 1/2" FEM ACME - 10mm MALE METRIC




VACUUM PUMP UNIONS

1/2" FEM. ACME -1/4" MALE FLARE **TO-77475**



TO-77500

VACUUM PUMP 'T' UNION MALE PIPE - 1/2" MALE ACME - 1/4" MF



CYLINDER UNION DUST CAPS


CO-80795

Specialized Service Tools

COMPRESSOR SERVICE **TOOLS**



DIPSTICK SANDEN SD5 SERIES



YORK AND TECUMSEH



TO-91180 UNIVERSAL CLUTCH HOLDING TOOL



TO-91212 DELPHI V5 CLUTCH HOLDING TOOL



TO-91240 SANDEN CLUTCH HOLDING TOOL



TO-92015 O-RING INSTALLER DELCO A6 (REPLACES TO-92010)



TO-92050 DELCO A6 PULLEY **INSTALLER**



TO-92900 DELCO A6 SEAL PROTECTOR



TO-92934 SEAL SLEEVE PROTECTOR SANDEN SD505 & 507



TO-92940 SANDEN SD508 SEAL **PROTECTOR**



TO-92970 SEAL SLEEVE **PROTECTOR** SANDEN TR & C SERIES



TO-93010 CLUTCH PLATE PULLER SANDEN SD505 & 507



TO-93040 UNIVERSAL PULLEY **PULLER**



TO-93100 **ROTOR & BEARING PULLER** SANDEN SD505 & 507



TO-93690 NIPPON DENSO **HUB REMOVER**

Specialized Service Tools

COMPRESSOR SERVICE TOOLS



TO-93800 UNIVERSAL O-RING REMOVER



TO-93892 DELCO A6 HUB REMOVER (use with TO-93895 INSTALLER)



TO-93895 DELCO A6 HUB INSTALLER (USE WITH TO-93892 HUB REMOVER)



TO-93897
DELPHI V5 HUB REMOVER
(USE WITH TO-93898
HUB REMOVER)



TO-93898

DELPHI V5 HUB INSTALLER
(USE WITH TO-93897
HUB REMOVER)



TO-94020 SEAL REMOVER-INSTALLER DELCO CERAMIC SEAL



TO-94035 SEAL REMOVER-INSTALLER DELCO STEEL SEAL



TO-94041

DELCO A6 AND R4

SEAL REMOVER - INSTALLER

(COMPLETE KIT)



TO-94060 SEAL SEAT REMOVER-INSTALLER DELCO A6; SANDEN SD508 (ALSO EARLY SD507)



TO-94257 SEAL REMOVER-INSTALLER SANDEN SD505; LATE SD507 AND TR SERIES



TO-94270 SEAL REMOVER-INSTALLER SANDEN EARLY SD507; SD508



TO-94295 SEAL SEAT REMOVER-INSTALLER SANDEN SD505; LATE SD507



TO-94320 SEAL REMOVER-INSTALLER SANDEN SD7H



TO-94375 SEAL REMOVER-INSTALLER SANDEN TRS